

Switching Power Supply : NS-1210, 1215, 1225, 1228 CE / LVD



Main Features:

- Short circuit and over voltage protection
- Output power rated at continuous service
- Binding post output terminals
- Precision regulation of output voltage
- Low peak-peak ripple of less than 0.3%
- External fuse access
- High surge capacity
- Heavy duty metal cabinet & power coating

Application:

- Communication equipment
- Auto mobile sound system
- Test equipment and appliances
- Portable entertainment equipment and appliances
- Vehicle accessories & DC lighting system
- Security system and CCTV
- Amateur (HAM) radio equipment
- Cooler boxes

Specifications:

Model	NS-1210	NS-1215	NS-1225	NS-1228
Input Voltage	AC 110V or 220V +/- 10% switchable			
Input frequency	47-63 Hz			
Polarity	Negative			
Output voltage	DC 13.8 fixed			
Continuous (13.8V)	8A	12A	22A	25A
Surge (13.8V)	10A	15A	25A	28A
Overvoltage protection	16V +/- 0.5V			
Ripple & Noise	Peak to peak ripple and noise less than 0.3%			
Efficiency	75%			
Dimension L/W/H (mm)	200 x 180 x 55			230 x 180 x 55
Net Weight	1.7 Kg		1.8 Kg	